

C E R T I F I C A T E

Päiväys: 16.2.2018

Meidän tilausnumero: 0485969
Asiakkaan tilausnumero: R.Wessman, 002592

TAMMINIITTY OY
ATT: AINE
KETJUTIE 4
FI-27710 KÖYLIÖ

Rivi	Tuote	Kuvaus	Viite	Sulatusnumero
1	4100301126	EN AW-5754 H22 4X1500X3000 EI PAP		17619042

Pyydetyt todistukset yllä oleville tilauksille lähetetään teille.

BE Group Oy Ab
PL 54 Helsingintie 50
FI-15101 LAHTI

Puhelinnumero: +358 3 825200
Faksinumero: +358 3 8252503

certificates@begroup.fi



impexmetal s.a.
ALUMINIUM KONIN

62-510 KONIN ul.Hutnicza 1

Tel. (063) 247 44 22

(063) 247 44 88

Fax. (063) 247 47 89

INSPECTION CERTIFICATE
EN 10204/3.1

No 127456/6

Date: 2018-01-27

ORDER No	P058437
-----------------	----------------

GOODS DESCRIPTION			
Alloy	Batch No	Dimensions [mm]	Temper
EN-AW 5754	127456/6	Thickness	4,000
		Width	1500,00
		Length	3000,00
			H22

CHEMICAL ANALYSIS [%]									
Heat/Melt No	Fe	Si	Cu	Mg	Mn	Cr	Ti	Zn	Other
17619042	0,330	0,261	0,054	2,935	0,276	0,043	0,027	0,037	

MECHANICAL AND OTHER PROPERTIES					
Slab/Coil No	Rm	R _{p0,2}	A ₅₀	Hardness	Other
	[MPa]	[MPa]	[%]	[HB, V]	
17619042	222	141	21	-	-

Tolerance of dimensions and the shape - positive result

WE HEREBY CERTIFY THAT THE GOODS COMPLY WITH YOUR ORDER AND NORM:

EN485-1,2,4; EN573-3; EN15088



1436-CPR-0032
2013

CENTRAL LABORATORY
Laboratory Foreperson
Waldemar Dobry

TRANSPORT and STORAGE CONDITIONS OF ALUMINIUM STRIPS AND SHEETS BY CUSTOMER

Strips (sheets) should be transported by covered, dry and clean means of transport preserving current regulation, protecting it from mechanical damage, humidity and harmful environmental factors.

Strips (sheets) should be stored in covered, dry and clean rooms protecting them from humidity and action of active chemicals. Protection of coil edges against mechanical damage should be taken into special attention. Butting face damage can cause difficulties in uncoiling process.

The storage temperature room should be stable. Changes of the temperature in stock cause that air moisture is condensed on the strip surface, in consequence of capillary activity, between coils, penetrates inside and inducing corrosion.

Disregard of above mentioned transport and storage conditions absolves supplier from responsibilities for material quality.