

Tilaja Purchaser  
TIBNOR OY  
NIINISTÖNKATU 7  
05800 HYVINKÄÄ FINLAND

Tilaus nro Order No.  
4501261624

Tilausvahvistus Order Confirmation  
23036

Vastaanottaja Consignee  
TIBNOR OY  
TUOTTAJANTIE 49  
60100 SEINÄJOKI FINLAND  
Asiakkaan merkki Shipping mark

Päivämäärä Date  
22.03.2021

Valmistajan merkki  
Mark of the Manufacturer



Todistus Certificate  
31

Laivaus Shipping

Laatumerkintä Quality Marking  
S355K2 J2 J0 JR N

Tarkastajan leima  
Stamp of Inspector

*Mxx*

Toimitustyyppi Delivery type  
PART DELIVERY

Sulatus nro levy nro Cast No. Plate No.  
X X X X X X X X X X X X X X X

Vastaanottajan leima  
Stamp of Surveyor

Muut leimaukset  
Other Stamps

Tuote Product  
HEAVY PLATES  
Laji Grade  
S355K2/J2/J0/JR+N EN 10025-2:2019  
Laatuselvitys Quality Specifications  
STEEL FOR GENERAL STRUCTURAL PURPOSES

Toleranssit Tolerances  
EN 10029:2010 CLASS A

Tekniset vaatimukset ja/tai viralliset määräykset Technical terms of Delivery and/or Official Regulations

Positio Item	Mitat mm Dimensions mm	Merkki Marke	Kpl Pcs	Paino kg Weight kg	Sulatus levy nro Cast plate No	SP nro SP No	UT	MT
-----------------	---------------------------	-----------------	------------	-----------------------	-----------------------------------	-----------------	----	----

**HOT ROLLED STEEL PLATES**

FLANGEABILITY (C) ACC. TO STEEL GRADE SPEC.; CEV MAX 0,41%

SURFACE CONDITION EN 10 163-2:2005 CLASS A1

010	10.00 X 2450	X 12000	4501261624	B001.A01676	STD	2	4704	67997	011	011
010	10.00 X 2450	X 12000				2	4704	67997	012	011

\*\*\* 4 9408

**Raah Steel Works**

Täten todistamme, että toimitus on tilausvahvistuksen mukainen.  
We hereby certify that the material described above has been tested and complies with the terms of the order confirmation.

Testaus ja tarkastus Testing and Inspection

*Minna Valkama*

**MINNA VALKAMA**

Valtuutettu tarkastaja Authorized inspection representative

Yhtiön nimi Company Name: SSAB Europe Oy  
Kotipaikka Registered Office: HÄMEENLINNA

Osoite Address: PL 93, P.O Box 93  
FIN-92101 RAAHE, FINLAND

Puhelin Telephone: 020 5911  
+358 20 5911

Y-tunnus Business ID: 2389445-7



Sulatus nro Cast No Schmelzen Nr. No de coulén № Плавки	Koe nro Test No Prüf Nr. Essai No № Пробы	Positio Item Pos. Poste Поз.	Cekv Ceq Caq Cég Cekv	Analyysi % Chemical composition % Chemisch Zusammensetzung % Composition Chimique % Анализ плавки % (*=ppm)													Päivämäärä Date Datum Date Дата			
				C	SI	MN	P	S	AL	NB	V	CU	CR	NI	MO	22.03.2021		AMH		
67997		010	.40	.150	.38	1.41	.008	.004	.031	.014	.006	.020	0.03	0.05	.005					

CEQ=C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15

### Raah Steel Works

Testaus ja tarkastus    Testing and Inspection    Испытание и контроль качества  
Prüfung und Kontrolle    Essais et Contrôle

Steel manufactured and supplied by Raah Steel Works is free from radiation.  
Производимая на металлургическом комбинате «Raah Steel Works» и поставляемая  
заказчику сталь не излучают радиации.

### MINNA VALKAMA

Valtuutettu tarkastaja    Authorized inspection representative    Уполномоченный инспектор  
Sachverständiger    Inspecteur autorisé

Yhtiön nimi Company Name:    SSAB Europe Oy    Osoite Address:    PL 93, P.O Box 93  
Kotipaikka Registered Office:    HÄMEENLINNA    FIN-92101 RAAHE, FINLAND

Puhelin Telephone:    020 5911  
+358 20 5911

Y-tunnus Business ID:    2389445-7

**Declaration of performance**  
(according to EU No 305/2011 and 574/2014)

DoP id. P011\_02

Hot rolled Plate product S355K2 / 1.0596  
according to  
EN 10025-2:2019  
for bolted, welded and riveted structures.

SSAB  
P.O Box 70  
101 20 Stockholm  
SWEDEN  
T: +46 8 45 45 700  
Email: info@ssab.com  
Website: ssab.com

TÜV NORD Systems GmbH & Co. KG  
Grosse Bahnstrasse 31  
D-22525 Hamburg  
Germany  
T: +49 40 8557 2368

Assessment system and verification for constancy  
of performance  
**System 2+**

The performance of the product identified in this document is  
in conformity with the set of declared performance. This declaration of performance  
is issued in accordance with Regulations (EU) No 305/2011 and 574/2014,  
under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Jarkko Matkala  
Vice President, hot rolled plate and strip products,  
SSAB Europe Oy, Raahе Steelworks  
Raahе 2015-06-09



05

0045-CPR-0573

EN 10025-1:2004

Dop id: P011_02 EN 10025-2:2019		Performance		Harmonized technical specification
S355K2	Thickness	Tolerances on the nominal thickness (acc. EN 10029 Class A unless otherwise stated)		EN 10025-1:2004
Tolerances on dimensions and shapes.	Nominal thickness (mm)	Lower	Upper	
		$3 \leq t < 5$	-0,3	
	$5 \leq t < 8$	-0,4	+0,8	
	$8 \leq t < 15$	-0,5	+0,9	
	$15 \leq t < 25$	-0,6	+1,0	
	$25 \leq t < 40$	-0,7	+1,3	
	$40 \leq t < 80$	-0,9	+1,7	
	$80 \leq t < 150$	-1,1	+2,1	
$150 \leq t < 250$	-1,2	+2,4		
Width	Nominal thickness	Tolerances		
		Lower	Upper	
	$t < 40$	0	+20	
	$40 \leq t < 150$	0	+25	
	$150 \leq t < 400$	0	+30	
Tolerances on width for plates with untrimmed edges (NK) shall be the subject of agreement between the manufacturer and purchaser at the time of enquiry and order				
Length	Nominal length	Tolerances		
	$l$	Lower	Upper	
	$l < 4000$	0	+20	
	$4000 \leq l < 6000$	0	+30	
	$6000 \leq l < 8000$	0	+40	
	$8000 \leq l < 10\ 000$	0	+50	
	$10\ 000 \leq l < 15\ 000$	0	+75	
	$15\ 000 \leq l < 20\ 000$	0	+100	
Tolerances on plates with nominal length $l > 20\ 000$ mm shall be agreed at the time of enquiry and order.				
Flatness	Nominal thickness $t$	Measuring length		
	$t$	1000	2000	
	$3 \leq t < 5$	9	14	
	$5 \leq t < 8$	8	12	
	$8 \leq t < 15$	7	11	
	$15 \leq t < 25$	7	10	
	$25 \leq t < 40$	6	9	
	$40 \leq t < 250$	5	8	

Yield strength	thickness mm	min (Mpa)	
	$\leq 16$	355	
	$> 16 \leq 40$	345	
	$> 40 \leq 63$	335	
	$> 63 \leq 80$	325	
	$> 80 \leq 100$	315	
	$> 100 \leq 150$	295	
	$> 150 \leq 200$	285	
$> 200 \leq 250$	275		
Tensile strength	thickness mm	min (Mpa)	max (Mpa)
	$< 3$	510	680
	$\geq 3 \leq 100$	470	630
	$> 100 \leq 150$	450	600
	$> 150 \leq 250$	450	600
Elongation	thickness mm	min %	
	$\geq 3 \leq 40$	20	
	$> 40 \leq 63$	19	
	$> 63 \leq 100$	18	
	$> 100 \leq 150$	18	
	$> 150 \leq 250$	17	
Impact strength	thickness mm	temperature, °C	min. energy, J
	$\leq 150$	-20	40
	$> 150 \leq 250$	-20	33
Weldability CEV	thickness mm	CEV max %	
	$\leq 30$	0,45	
	$> 30 \leq 40$	0,47	
	$> 40 \leq 150$	0,47	
	$> 150 \leq 250$	0,49	
Durability (chemical composition)	element	Value	
		$\leq 30$	$> 30$
	C, max	0,20	0,22
	Si, max	0,55	
	Mn, max	1,60	
	P, max	0.025	
	S, max	0.025	
	N, max		
	Cu, max	0.55	
	Ni, max	0,42	
	Cr, max	0,29	
	Mo, max	0,11	

**Declaration of performance**  
(according to EU No 305/2011 and 574/2014)

DoP id. P010\_02

Hot rolled Plate product S355J2 / 1.0577  
according to  
EN 10025-2:2019  
for bolted, welded and riveted structures.

SSAB  
P.O Box 70  
101 20 Stockholm  
SWEDEN  
T: +46 8 45 45 700  
Email: info@ssab.com  
Website: ssab.com

TÜV NORD Systems GmbH & Co. KG  
Grosse Bahnstrasse 31  
D-22525 Hamburg  
Germany  
T: +49 40 8557 2368

Assessment system and verification for constancy  
of performance  
**System 2+**

The performance of the product identified in this document is  
in conformity with the set of declared performance. This declaration of performance  
is issued in accordance with Regulations (EU) No 305/2011 and 574/2014,  
under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Jarkko Matkala  
Vice President, hot rolled plate and strip products,  
SSAB Europe Oy, Raahе Steelworks  
Raahе 2015-06-09



05

0045-CPR-0573

EN 10025-1:2004

Dop id: P010_02 EN 10025-2:2019		Performance		Harmonized technical specification
S355J2	Thickness	Tolerances on the nominal thickness (acc. EN 10029 Class A unless otherwise stated)		EN 10025-1:2004
Tolerances on dimensions and shapes.	Nominal thickness (mm)	Lower	Upper	
		$3 \leq t < 5$	-0,3	
	$5 \leq t < 8$	-0,4	+0,8	
	$8 \leq t < 15$	-0,5	+0,9	
	$15 \leq t < 25$	-0,6	+1,0	
	$25 \leq t < 40$	-0,7	+1,3	
	$40 \leq t < 80$	-0,9	+1,7	
	$80 \leq t < 150$	-1,1	+2,1	
$150 \leq t < 250$	-1,2	+2,4		
Width	Nominal thickness	Tolerances		
		Lower	Upper	
	$t < 40$	0	+20	
	$40 \leq t < 150$	0	+25	
	$150 \leq t < 400$	0	+30	
Tolerances on width for plates with untrimmed edges (NK) shall be the subject of agreement between the manufacturer and purchaser at the time of enquiry and order				
Length	Nominal length	Tolerances		
	$l$	Lower	Upper	
	$l < 4000$	0	+20	
	$4000 \leq l < 6000$	0	+30	
	$6000 \leq l < 8000$	0	+40	
	$8000 \leq l < 10\ 000$	0	+50	
	$10\ 000 \leq l < 15\ 000$	0	+75	
	$15\ 000 \leq l < 20\ 000$	0	+100	
Tolerances on plates with nominal length $l > 20\ 000$ mm shall be agreed at the time of enquiry and order.				
Flatness	Nominal thickness $t$	Measuring length		
	$t$	1000	2000	
	$3 \leq t < 5$	9	14	
	$5 \leq t < 8$	8	12	
	$8 \leq t < 15$	7	11	
	$15 \leq t < 25$	7	10	
	$25 \leq t < 40$	6	9	
	$40 \leq t < 250$	5	8	

Yield strength	thickness mm	min (Mpa)	
	$\leq 16$	355	
	$> 16 \leq 40$	345	
	$> 40 \leq 63$	335	
	$> 63 \leq 80$	325	
	$> 80 \leq 100$	315	
	$> 100 \leq 150$	295	
	$> 150 \leq 200$	285	
$> 200 \leq 250$	275		
Tensile strength	thickness mm	min (Mpa)	max (Mpa)
	$< 3$	510	680
	$\geq 3 \leq 100$	470	630
	$> 100 \leq 150$	450	600
	$> 150 \leq 250$	450	600
Elongation	thickness mm	min %	
	$\geq 3 \leq 40$	20	
	$> 40 \leq 63$	19	
	$> 63 \leq 100$	18	
	$> 100 \leq 150$	18	
	$> 150 \leq 250$	17	
Impact strength	thickness mm	temperature, °C	min. energy, J
	$\leq 150$	-20	27
	$> 150 \leq 250$	-20	27
Weldability CEV	thickness mm	CEV max %	
	$\leq 30$	0,45	
	$> 30 \leq 40$	0,47	
	$> 40 \leq 150$	0,47	
	$> 150 \leq 250$	0,49	
Durability (chemical composition)	element	Value	
		$\leq 30$	$> 30$
	C, max	0,20	0,22
	Si, max	0,55	
	Mn, max	1,60	
	P, max	0.025	
	S, max	0.025	
	N, max		
	Cu, max	0.55	
	Ni, max	0,42	
	Cr, max	0,29	
	Mo, max	0,11	

**Declaration of performance**  
(according to EU No 305/2011 and 574/2014)

DoP id. P009\_02

Hot rolled Plate product S355J0 / 1.0553  
according to  
EN 10025-2:2019  
for bolted, welded and riveted structures.

SSAB  
P.O Box 70  
101 20 Stockholm  
SWEDEN  
T: +46 8 45 45 700  
Email: info@ssab.com  
Website: ssab.com

TÜV NORD Systems GmbH & Co. KG  
Grosse Bahnstrasse 31  
D-22525 Hamburg  
Germany  
T: +49 40 8557 2368

Assessment system and verification for constancy  
of performance  
**System 2+**

The performance of the product identified in this document is  
in conformity with the set of declared performance. This declaration of performance  
is issued in accordance with Regulations (EU) No 305/2011 and 574/2014,  
under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Jarkko Matkala  
Vice President, hot rolled plate and strip products,  
SSAB Europe Oy, Raahе Steelworks  
Raahе 2015-06-09



05

0045-CPR-0573  
EN 10025-1:2004



Dop id: P009_02 EN 10025-2:2019		Performance		Harmonized technical specification
S355J0	Thickness	Tolerances on the nominal thickness (acc. EN 10029 Class A unless otherwise stated)		EN 10025-1:2004
Tolerances on dimensions and shapes.	Nominal thickness (mm)	Lower	Upper	
		$3 \leq t < 5$	-0,3	
	$5 \leq t < 8$	-0,4	+0,8	
	$8 \leq t < 15$	-0,5	+0,9	
	$15 \leq t < 25$	-0,6	+1,0	
	$25 \leq t < 40$	-0,7	+1,3	
	$40 \leq t < 80$	-0,9	+1,7	
	$80 \leq t < 150$	-1,1	+2,1	
$150 \leq t < 250$	-1,2	+2,4		
Width	Nominal thickness	Tolerances		
		Lower	Upper	
	$t < 40$	0	+20	
	$40 \leq t < 150$	0	+25	
	$150 \leq t < 400$	0	+30	
Tolerances on width for plates with untrimmed edges (NK) shall be the subject of agreement between the manufacturer and purchaser at the time of enquiry and order				
Length	Nominal length	Tolerances		
	$l$	Lower	Upper	
	$l < 4000$	0	+20	
	$4000 \leq l < 6000$	0	+30	
	$6000 \leq l < 8000$	0	+40	
	$8000 \leq l < 10\ 000$	0	+50	
	$10\ 000 \leq l < 15\ 000$	0	+75	
$15\ 000 \leq l < 20\ 000$	0	+100		
Tolerances on plates with nominal length $l > 20\ 000$ mm shall be agreed at the time of enquiry and order.				
Flatness	Nominal thickness $t$	Measuring length		
	$t$	1000	2000	
	$3 \leq t < 5$	9	14	
	$5 \leq t < 8$	8	12	
	$8 \leq t < 15$	7	11	
	$15 \leq t < 25$	7	10	
	$25 \leq t < 40$	6	9	
	$40 \leq t < 250$	5	8	

Yield strength	thickness mm	min (Mpa)	
	$\leq 16$	355	
	$> 16 \leq 40$	345	
	$> 40 \leq 63$	335	
	$> 63 \leq 80$	325	
	$> 80 \leq 100$	315	
	$> 100 \leq 150$	295	
	$> 150 \leq 200$	285	
$> 200 \leq 250$	275		
Tensile strength	thickness mm	min (Mpa)	max (Mpa)
	$< 3$	510	680
	$\geq 3 \leq 100$	470	630
	$> 100 \leq 150$	450	600
	$> 150 \leq 250$	450	600
Elongation	thickness mm	min %	
	$\geq 3 \leq 40$	20	
	$> 40 \leq 63$	19	
	$> 63 \leq 100$	18	
	$> 100 \leq 150$	18	
	$> 150 \leq 250$	17	
Impact strength	thickness mm	temperature, °C	min. energy, J
	$\leq 150$	0	27
	$> 150 \leq 250$	0	27
Weldability CEV	thickness mm	CEV max %	
	$\leq 30$	0,45	
	$> 30 \leq 40$	0,47	
	$> 40 \leq 150$	0,47	
	$> 150 \leq 250$	0,49	
Durability (chemical composition)	element	Value	
		$\leq 30$	$> 30$
	C, max	0,20	0,22
	Si, max	0,55	
	Mn, max	1,60	
	P, max	0.030	
	S, max	0.030	
	N, max	0,012	
	Cu, max	0.55	
	Ni, max	0,42	
	Cr, max	0,29	
	Mo, max	0,11	

**Declaration of performance**  
(according to EU No 305/2011 and 574/2014)

DoP id. P008\_02

Hot rolled Plate product S355JR / 1.0045  
according to  
EN 10025-2:2019  
for bolted, welded and riveted structures.

SSAB  
P.O Box 70  
101 20 Stockholm  
SWEDEN  
T: +46 8 45 45 700  
Email: info@ssab.com  
Website: ssab.com

TÜV NORD Systems GmbH & Co. KG  
Grosse Bahnstrasse 31  
D-22525 Hamburg  
Germany  
T: +49 40 8557 2368

Assessment system and verification for constancy  
of performance  
**System 2+**

The performance of the product identified in this document is  
in conformity with the set of declared performance. This declaration of performance  
is issued in accordance with Regulations (EU) No 305/2011 and 574/2014,  
under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Jarkko Matkala  
Vice President, hot rolled plate and strip products,  
SSAB Europe Oy, Raahе Steelworks  
Raahе 2015-06-09



05

0045-CPR-0573

EN 10025-1:2004

Dop id: P008_02 EN 10025-2:2019		Performance		Harmonized technical specification	
S355JR	Thickness	Tolerances on the nominal thickness (acc. EN 10029 Class A unless otherwise stated)		EN 10025-1:2004	
Tolerances on dimensions and shapes.	Thickness	Nominal thickness (mm)	Lower		Upper
		$3 \leq t < 5$	-0,3		+0,7
		$5 \leq t < 8$	-0,4		+0,8
		$8 \leq t < 15$	-0,5		+0,9
		$15 \leq t < 25$	-0,6		+1,0
		$25 \leq t < 40$	-0,7		+1,3
		$40 \leq t < 80$	-0,9		+1,7
		$80 \leq t < 150$	-1,1		+2,1
	$150 \leq t < 250$	-1,2	+2,4		
Width	Nominal thickness		Tolerances		
		Lower	Upper		
	$t < 40$	0	+20		
	$40 \leq t < 150$	0	+25		
	$150 \leq t < 400$	0	+30		
Tolerances on width for plates with untrimmed edges (NK) shall be the subject of agreement between the manufacturer and purchaser at the time of enquiry and order					
Length	Nominal length		Tolerances		
		Lower	Upper		
	$l < 4000$	0	+20		
	$4000 \leq l < 6000$	0	+30		
	$6000 \leq l < 8000$	0	+40		
	$8000 \leq l < 10\ 000$	0	+50		
	$10\ 000 \leq l < 15\ 000$	0	+75		
	$15\ 000 \leq l < 20\ 000$	0	+100		
Tolerances on plates with nominal length $l > 20\ 000$ mm shall be agreed at the time of enquiry and order.					
Flatness	Nominal thickness t		Measuring length		
		1000	2000		
	$3 \leq t < 5$	9	14		
	$5 \leq t < 8$	8	12		
	$8 \leq t < 15$	7	11		
	$15 \leq t < 25$	7	10		
	$25 \leq t < 40$	6	9		
	$40 \leq t < 250$	5	8		

Yield strength	thickness mm	min (Mpa)	
	$\leq 16$	355	
	$> 16 \leq 40$	345	
	$> 40 \leq 63$	335	
	$> 63 \leq 80$	325	
	$> 80 \leq 100$	315	
	$> 100 \leq 150$	295	
	$> 150 \leq 200$	285	
	$> 200 \leq 250$	275	
Tensile strength	thickness mm	min (Mpa)	max (Mpa)
	$< 3$	510	680
	$\geq 3 \leq 100$	470	630
	$> 100 \leq 150$	450	600
	$> 150 \leq 250$	450	600
Elongation	thickness mm	min %	
	$\geq 3 \leq 40$	20	
	$> 40 \leq 63$	19	
	$> 63 \leq 100$	18	
	$> 100 \leq 150$	18	
	$> 150 \leq 250$	17	
Impact strength	thickness mm	temperature, °C	min. energy, J
	$\leq 150$	20	27
	$> 150 \leq 250$	20	27
Weldability CEV	thickness mm	CEV max %	
	$\leq 30$	0,45	
	$> 30 \leq 40$	0,47	
	$> 40 \leq 150$	0,47	
	$> 150 \leq 250$	0,49	
Durability (chemical composition)	element	Value	
	C, max	0,24	
	Si, max	0,55	
	Mn, max	1.60	
	P, max	0.035	
	S, max	0.035	
	N, max	0,012	
	Cu, max	0.55	
	Ni, max	0,42	
	Cr, max	0,29	
	Mo, max	0,11	