ArcelorMittal

ARCELORMITTAL FRANCE MARDYCK
ROUTE DE SPYCKER
BP 129 F-59760 GRANDE SYNTHE
A01

# INSPECTION CERTIFICATE EN 10204-3.1

A02

N° 0081360135 Page 1
A09/A03

Mill's identification: **MK** A04

Hot rolled pickled coil B03

| Sizes | Length | Width | Thickness |
|---|---|---|---|
| | B09 | B10 | B11 |
| | | 1500,00 | 3,000 |

CDC: According to specifications
BL : As rolled
D : Stress relieving
R : Annealed

Inspection organism: METALLURGIE QUALITE A05

Customer and/or consignee: Oy AluSteel Ab, Hepokarintie 9, 23500 UUSIKAUPUNKI Finland A06

Customer's Order Nbr: 38908 A07

Mill's Order Nbr: GH14ALU003 000001 A08

Grade and technical specifications

**Quality :** Amstrong355MC AFCS **Standard :** AFCS

| Coating | Mass | Chemical treatment | Spangle | Appearence | Protection |
|---|---|---|---|---|---|
| **Face 1** | | without treatme | | A | STD PROTECTION |
| **Face 2** | | without treatme | | A | STD PROTECTION |

**Article reference :** B01/B02

Delivery condition: CDC B04

Treatment of test samples: CDC B05

| | Longitudinal tensile test | | | Transverse tensile test | | | | Roughness (3) | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Coating (4) | | | | | | | | | | | | | | | |
| Product identification | Heat number | P | Net Weight | Ys | Ts | EL% | YS | TS | EL% | n (5) | | | Ra | Peaks | | | | | | | | | | | | | | | | | | |
| | | (1) | Kg | MPA | MPA | 2 (2) | | | 2 (2) | | | | µm | | | | Edge | Center | Edge | Aver. | Edge | Center | Edge | Aver. | Aver. | | | | | | | |
| Minimum | | | | 355 | 430 | 25 | 380 | 440 | 24 | | | | | | | | | | | | | | | | | | | | | | | |
| Maximum | | | | 435 | 520 | | 460 | 530 | | | | | | | | | | | | | | | | | | | | | | | | |
| B07 | C00 | C01 | | C11 | C12 | C13 | C11 | C12 | C13 | | | | | | | | | | | | | | | | | | | | | | | |
| 27669700 | 8641059003 | F | 24160 | 413 | 463 | 39 | | | | 0,180 | | | | | | | | | | | | | | | | | | | | | | |
| 27671200 | 8641058914 | F | 27140 | 416 | 468 | 38 | | | | 0,170 | | | | | | | | | | | | | | | | | | | | | | |
| 27673400 | 8641058595 | F | 23980 | 432 | 481 | 41 | | | | 0,190 | | | | | | | | | | | | | | | | | | | | | | |
| 27731900 | 8641059921 | F | 28640 | 411 | 464 | 39 | | | | 0,180 | | | | | | | | | | | | | | | | | | | | | | |

Chemical analysis in % ( * : product analysis )

| Heat number | C | Mn | P | S | Si | Al | N | Ti | Nb | V | Ni | Cr | Cu | Mo |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| C00 | C71 | C72 | C73 | C74 | C75 | C76 | C77 | C78 | C79 | C80 | C81 | C82 | C83 | C84 |
| Minimum | | | | | | 0,0150 | | | | | | | | |
| Maximum | 0,1000 | 1,4000 | 0,0200 | 0,0150 | 0,0300 | | | 0,1500 | 0,0650 | 0,2000 | | | | |
| 8641059003 | 0,0594 | 0,3542 | 0,0150 | 0,0096 | 0,0079 | 0,0282 | 0,0043 | 0,0007 | 0,0233 | 0,0004 | 0,0122 | 0,0291 | 0,0070 | 0,0011 |
| 8641058914 | 0,0702 | 0,3457 | 0,0122 | 0,0073 | 0,0038 | 0,0376 | 0,0026 | 0,0004 | 0,0249 | 0,0001 | 0,0226 | 0,0267 | 0,0160 | 0,0012 |
| 8641058595 | 0,0727 | 0,5173 | 0,0179 | 0,0057 | 0,0073 | 0,0412 | 0,0039 | 0,0010 | 0,0247 | 0,0002 | 0,0145 | 0,0277 | 0,0082 | 0,0011 |
| 8641059921 | 0,0621 | 0,3586 | 0,0092 | 0,0076 | 0,0082 | 0,0373 | 0,0036 | 0,0005 | 0,0225 | 0,0004 | 0,0136 | 0,0208 | 0,0083 | 0,0007 |

(1) Location
D : Head
M : Middle
F : Tail
C01

(2) 1: LO = 80mm
2: LO = 5.65√SO
3: JIS 25x50
C10

(3)

(4)

(5) n : Longitudinal

We hereby certify that the above cited shipment was produced according to the technical specifications of the contract and that, with inspection and tests completed, it meets those specifications as well as all norms and standards referred to in the contract. Z01

Inspection of markings, surface, sizes : satisfactory. D01

Date 14/12/21
Receiving Agent
S.MATEOS

349 Z02/Z03