

EN 10204 - 3.1
22092130-EN-0

Business Unit / QCM



BA Quarto Plate, Quarto Plate Europe

Date Datum Date
28-Sep-2022

Load, Ladung, Charge No
234616

Acknowledged ID, Bestätigung, Commande ID
300642016

Your ref, Ihre Ref., Votre ref 022841-1	Requirements, Anforderungen, Exigences EN 10088-4:2009 EN 10088-2:14 EN 10028-7 (PED 2014/68/EU):16 ASME SA-240M Code Sect. II. Part A:2021 ASTM A240M:20
Buyer, Besteller, Acheteur Ovako Metals Oy Ab ATOMITIE 5 A 00370, HELSINKI FINLAND	
Consignee, Empfänger, Lieu de livraison Ovako Metals Oy Ab	

Mark of Manufacturer Zeichen des Lieferwerkes Signe de producteur 	Process Erschmelzungsart Mode de fusion E+AOD	Inspector's stamp Zeichen des Sachverständigen Poinçon de l'expert 	Grade, Werkstoff, Nuance Outokumpu 2205 1.4462 UNS S31803
--	--	---	--

Product, Erzeugnisform, Produit
Stainless steel hot rolled, Plate, 1D/No.1, Cut edge

Line Reihe Ligne	Item Position Poste	Heat-Lot No Schmelze-Lot Nr Coulée n° - Lot No	Size Abmessungen Dimensions	Pieces Stückzahl Nombre	Quantity/unit, Menge/Einheit, Quantité/Unité
1	1	523075-436951:0	10,0 X 1500,0 X 3000,0 mm	9	

Plate No, Blech Nr, Tôle No 1	3227 3301-1,-2,-3,-3401-1,-2,-3,-3501-1,-2,-3
----------------------------------	---

Chemical composition - Chemische Zusammensetzung - Composition chimique %
Heat - Schmelze - coulee No

	C	Si	Mn	P	S	Cr	Ni	Mo	N				
Min						21.0	4.50	2.50	0.10				
Max	0.030	1.00	2.00	0.030	0.015	23.0	6.50	3.50	0.20				
523075	0.019	0.55	1.54	0.029	0.001	22.5	5.17	2.86	0.18				

Distribution Certificate via e-Services.	Direct. T = Transverse L = Longitudinal	Top/Bot F = Front B = Back	Form P = Flat C = Round	Location 1 = Center 2 = Close to Surface 3 = Standard 4 = At 1/4 of thickness
---	---	----------------------------------	-------------------------------	---

Test results - Prüfergebnisse - Résultats des essais (1N/mm² = 1MPa)

Mechanical properties
Tensile testing/Hardness Rockwell C

Plate-no	Direct.	Top/Bot	Location	Form	Temp. °C	Rp 0,2 MPa	Rm MPa	A5 %	A50 %	HRC HRC
Min						460	640	25	25	
Max							840			31
3501	T	F	2	P	20	598	793	38	40	21


Charpy impact test (V-notch) EN ISO 148-1 10x7.5

Plate-no	Direct.	Top/Bot	Location	Form	Temp. °C	Value1 J	Value2 J	Value3 J	Average J
Min									83
3501	T	F	2	P	20	172	206	189	189

Other Information
Country of melt: Sweden
Manufactured in Sweden.
Solution annealed at 1100°C and Quenched in water.
Dimensional control, visual inspection and grade check (PMI): Approved
Approved acc. to AD2000-Merkblatt W0 and certified acc. to
Pressure Equipment Directive (2014/68/EU) by
TUEV NORD, notified body, reg.no. 0045.
Construction Products Regulation (305/2011/EU)
The Declaration of Performance (DoP), see www.outokumpu.com.

The results comply with the Requirements of the order - Die gestellten Anforderungen sind erfüllt - Les résultats sont conformes aux exigences de la commande







EN 10204 - 3.1
22092130-EN-0

Business Unit / QCM
BA Quarto Plate, Quarto Plate Europe

Date Datum Date
28-Sep-2022

Load, Ladung, Charge No
234616

Acknowledged ID, Bestätigung, Commande ID
300642016

Tolerance	Standard	Class
Flatness tolerance	EN 18286/A480/M/EN 10029	ISO 18286 N/A480/M/EN 10029 N
Length	EN 18286/A480/M/EN 10029	ISO 18286 A/A480/M/EN 10029
Thickness	EN 18286/A480/M/EN 10029	ISO 18286/A480/M/EN 10029 B
Width	EN 18286/A480/M/EN 10029	ISO 18286 A/A480/M/EN 10029

The results comply with the requirements of the order - Die gestellten Anforderungen sind erfüllt - Les résultats sont conformes aux exigences de la commande

Outokumpu Stainless AB
BA Quarto Plate, Quarto Plate Europe
SE - 693 81 DEGERFORS
SWEDEN
Regoffice: SWEDEN

V.A.T no: SE556001874801
, Regno: 556001-8748

Computer generated original
Quality Inspector

Liselotte Andersen

