

		MILL CERTIFICATE BS EN 10204/3.1 CERTIFICAT DE RECEPTION NF EN 10204/3.1 ABNAHMEPRUEFZEUGNIS DIN EN 10204/3.1										N-Nr-N 23K0011717-01 V01																					
		Certified acc.PED 2014/68/EU Annex I 4.3 by Certification Body 0036 of TUV SUD Industrie Service GmbH with cert.No.:314/2007/MUC.Renounced of counter signature agreed by TÜV SÜD (9/5/2007).Approved acc.AD 2000-Merkblatt W0/TRD 100 by TÜV SÜD Industrie Service GmbH.Confirmation letter from TÜVSÜD Industrie Service GmbH of 07/05/2010 about the uniformity of coils acc.AD2000 W2 4.1.1																															
Correspondentieadres: Aperam Genk Swinnenwijerweg 5, Poort Genk 7523 3600 Genk, Belgium Tel. +32 (0)89 30 21 11		Tech.Req.:AD 2000 W2 -- AD 2000 W10 -- EN 13445-2																															
Manufacturer's works order number N° de la commande usine productrice Werksauftragsnummer 80833214/01-08457/EK0/01		Surveyor's mark Cachet de l'expert Stempel des Werkssachverstaendigen 		Purchaser and/or consignee Client et/ou destinataire Besteller und/oder Empfaenger APERAM SS&S HAAN Aperam Allee 1 42781 Haan DEUTSCHLAND				Purchaser's order number N° de commande client Kundenbestellnummer 302897862																									
Product - Produit - Erzeugnis COILS, HOT ROLLED, ANNEALED AND PICKLED COILS, LAMINE A CHAUD, RECUITS + DECAPE COILS, WARMGEWALZT, GEGLUEHT UND GEBEIZT		Steelmaking process Mode d'elaboration de l'acier - Stahlherstellungsverfahren Prod.proces: Electric arc furnace - VOD/AOD - Continuous casting Proc.fabric.: Four à arc - VOD/AOD - Coulée continue Fertigungsablauf: Elektro-Ofen - VOD/AOD - Stranggussanlage		Customer article number N.articlé client Artikelnummer des Kunden ART000104																													
Steel designation Désignation de l'acier Stahlbezeichnung EN 10028-7-2016 1.4307 / 1.4301 EN 10088-2-2014 1.4307 / 1.4301 ASTM A 240-2022 TYPE 304L / 304 ASME SA 240-2021 TYPE 304L / 304 EN 10088-4-2009 1.4307 / 1.4301		Finish Présentation Ausfuehrung ID ID NO 1 NO 1 ID		Any supplementary requirements Prescriptions supplémentaires - Zusätzliche Anforderungen				Product delivery condition Etat de livraison du produit - Lieferzustand Solution Annealing Hypertrempe 1050 °C Lösungsglühen Forced air-water/air forcé-eau Geblaese Luft-Wasser																									
ASME-CODE SECT.2 PART A // NACE MR 0175 / ISO 15156-1 / ISO 15156-3 -- NACE MR 0103 / ISO 17945 // ASTM A480 / A480M -- ASME SA480 / SA480M // CORR. TEST: ASTM A262-E: OK // CORROSION INTERGRANULAIRE SELON ISO 3651/2:OK																																	
Identification of the product Identification du produit - Identifizierung des Erzeugnisses MELTED IN BELGIUM, MADE IN BELGIUM		Dimensions Dimensions - Abmessungen Thickness B09 Epaisseur - Staerke 12.00 mm				Width B10 Largeur - Breite 1500.00 mm		Length B11 Longueur - Laenge		Number of pieces B08 Nb de pièces - Stueckzahl 1		Net weight B13 Poids net - netto Gewicht 27360 KG																					
CHEMICAL ANALYSIS - ANALYSE CHIMIQUE - CHEMISCHE ZUSAMMENSETZUNG																																	
		C		Si		Mn		Ni		Cr		Mo		Ti		N		S		P		Co											
Required -Exigé % mini Anforderung. %maxi		0.030		0.75		2.00		8.00 10.50		18.00 19.50						0.100		0.015		0.045													
Cast Analysis Analyse coulee Analyse Schmelze		0.021		0.41		1.42		8.01		18.02				0.073		0.001		0.034		0.186													
		C71		C72		C73		C74		C75		C76		C77		C78		C79		C80		C81		C82		C83		C84		C85		C86	
Positive material identification carried out : OK Tests de vérification de la conformité de la nuance fournie : OK Verwechslungsprüfung wurde durchgeführt : OK														D52																			
Location (1)		MECHANICAL PROPERTIES - PROPRIETES MECANIQUES - MECHANISCHE WERTE EN ISO 6892-1 B / A-SA 370										C20																					
		Room temperature - Température ambiante - Raumtemperatur										Test temperature (°C) :		C03																			
Direction (2)		Yield or proof strength Limite d'élasticité Dehngrenze MPa				Tensile Strength Résistance à la traction Zugfestigkeit MPa				Elongation after fracture Allongement après rupt. Bruchdehnung %		Hardness Dureté Haerte		Yield or proof strength Limite d'élasticité Dehngrenze MPa		Tensile str. Résist. MPa Zugfestigkeit		Elongation % Allongement. Bruchdehnung															
		Rp0.2%		Rp1%		Rm		A5		50mm		HRBW		Rp0.2%		Rp1%		Rm		A5													
1 T		mini		210		250		520		45		45		92																			
2 T		maxi		370		415		700		56		54		89																			
		C11		C14		C12		C13		C15		C31		C16		C17		C18		C19													
Impact strength test Essai de résilience Kerbschlagzähigkeitstest		C40		t(°c)		C44																											
		C42																															
Location of the sample (1) Emplacement de l'échantillon Lage des Probenabschnittes 1. Front - Début - Anfang 2. Back - Fin - Ende 3. Middle - Milieu - Mitte		The delivery is in accordance with the order La fourniture est conforme aux exigences de la commande Die lieferung entspricht den Bestellbedingungen				Packing list Avis d'expédition Lieferscheinnummer 2023032475-102381				Organisation inspection Organisme et/ou service contrôle Ueberwachungsabteilung Quality Department 28/3/2023 The inspector Le responsable Der Werkssachverstaendige  R. Vliegen																							
		C01				Z01				A10		A05																					
Direction of the test pieces (2) Orientation des éprouvettes Probenrichtung T. Transverse - Travers - Quer L. Longitudinal - Long - Laengs		Marking, inspection and measurement : without objection Contrôle de marquage, d'aspect et de dimensions : satisfaisants Pruefung der Stempelung, des Oberflaechenaspekts und der Abmessungen : ohne Beanstandung				Internal cleanliness: A: B: C: D:				C57																							
		C02				D01																											