

		MILL CERTIFICATE BS EN 10204/3.1 CERTIFICAT DE RECEPTION NF EN 10204/3.1 ABNAHMEPRUEFZEUGNIS DIN EN 10204/3.1										N-Nr-N 23K0026674-01 V01													
		Certified acc.PED 2014/68/EU Annex I 4.3 by Certification Body 0036 of TUV SUD Industrie Service GmbH with cert.No.:314/2007/MUC.Renounced of counter signature agreed by TÜV SÜD (9/5/2007).Approved acc.AD 2000-Merkblatt W0/TRD 100 by TÜV SÜD Industrie Service GmbH.Confirmation letter from TÜVSÜD Industrie Service GmbH of 07/05/2010 about the uniformity of coils acc.AD2000 W2 4.1.1																							
Correspondentieadres: Aperam Genk Swinnenwijerweg 5, Poort Genk 7523 3600 Genk, Belgium Tel. +32 (0)89 30 21 11		Tech.Req.:AD 2000 W2 -- AD 2000 W10 -- EN 13445-2																							
Manufacturer's works order number N° de la commande usine productrice Werksauftragsnummer 80861002/01-08457/FU9/01		Surveyor's mark Cachet de l'expert Stempel des Werkssachverstaendigen 		Purchaser and/or consignee Client et/ou destinataire Besteller und/oder Empfaenger APERAM SS&S HAAN Aperam Allee 1 42781 Haan DEUTSCHLAND				Purchaser's order number N° de commande client Kundenbestellnummer 307901572																	
Product - Produit - Erzeugnis COILS, HOT ROLLED, ANNEALED AND PICKLED COILS, LAMINE A CHAUD, RECUITS + DECAPE COILS, WARMGEWALZT, GEGLUEHT UND GEBEIZT				Customer article number N.article client Artikelnummer des Kunden ART000102																					
Steel designation Désignation de l'acier Stahlbezeichnung EN 10028-7-2016 1.4307 / 1.4301 EN 10088-2-2014 1.4307 / 1.4301 ASTM A 240-2023 TYPE 304L / 304 ASME SA 240-2021 TYPE 304L / 304 EN 10088-4-2009 1.4307 / 1.4301		Finish Présentation Ausfuehrung ID ID NO 1 NO 1 ID		Steelmaking process Mode d'elaboration de l'acier - Stahlherstellungsverfahren Prod.proces: Electric arc furnace - VOD/AOD - Continuous casting Proc.fabric.: Four à arc - VOD/AOD - Coulée continue Fertigungsablauf: Elektro-Ofen - VOD/AOD - Stranggussanlage				Product delivery condition Etat de livraison du produit - Lieferzustand Solution Annealing Hypertrempe 1050 °C Lösungsglühen Forced air-water/air forcé-eau Geblaese Luft-Wasser																	
ASME-CODE SECT.2 PART A // NACE MR 0175 / ISO 15156-1 / ISO 15156-3 -- NACE MR 0103 / ISO 17945 // ASTM A480 / A480M -- ASME SA480 / SA480M // CORR. TEST: ASTM A262-E: OK // CORROSION INTERGRANULAIRE SELON ISO 3651/2:OK																									
Identification of the product Identification du produit - Identifizierung des Erzeugnisses MELTED IN BELGIUM, MADE IN BELGIUM		Dimensions Dimensions - Abmessungen Thickness B09 Epaisseur - Staerke 10.00 mm				Width B10 Largeur - Breite 1500.00 mm		Length B11 Longueur - Laenge		Number of pieces B08 Nb de pièces - Stueckzahl 1															
Coil n. N.Bobine - Band Nr. 31850516		Heat n. N.Coulée - Schmelz Nr. 813450								Net weight B13 Poids net - netto Gewicht 20060 KG															
CHEMICAL ANALYSIS - ANALYSE CHIMIQUE - CHEMISCHE ZUSAMMENSETZUNG																									
		C		Si		Mn		Ni		Cr		Mo		Ti		N		S		P		Co			
Required -Exigé %mini Anforderung. %maxi		0.030		0.75		2.00		8.00 10.50		18.00 19.50						0.100		0.015		0.045					
Cast Analysis Analyse coulée Analyse Schmelze		0.025		0.38		1.41		8.00		18.04				0.074		0.001		0.039		0.231					
		C71		C72		C73		C74		C75		C76		C77		C78		C79		C80		C81		C82	
Positive material identification carried out : OK Tests de vérification de la conformité de la nuance fournie : OK Verwechslungsprüfung wurde durchgeführt : OK														D52											
Location (1)		MECHANICAL PROPERTIES - PROPRIETES MECANIQUES - MECHANISCHE WERTE EN ISO 6892-1 B / A-SA 370										C20													
		Room temperature - Température ambiante - Raumtemperatur										Test temperature (°C) :		C03											
Direction (2)		Yield or proof strength Limite d'élasticité Dehngrenze MPa		Tensile Strength Résistance à la traction Zugfestigkeit MPa		Elongation after fracture Allongement après rupt. Bruchdehnung %		Hardness Dureté Haerte		Yield or proof strength Limite d'élasticité Dehngrenze MPa		Tensile str. Résist. MPa Zugfestigkeit		Elongation % Allongement. Bruchdehnung											
		Required Exigé Anforderung		Rp0.2% Rp1%		Rm		A5 50mm HRBW		Rp0.2% Rp1%		Rm		A5											
1 T		mini maxi		210 250		520 700		45 45		92															
2		Obtained Obtenu Ergebnisse		339 381		624		56 54		87 85															
		C11		C14		C12		C13		C15		C31		C16		C17		C18		C19					
Impact strength test Essai de résilience Kerbschlagzähigkeitstest				Corrosion test Test de corrosion Korrosionstest																					
		C40		C44																					
						EN ISO 3651/2 - A:OK		C50		C51		C52		C53		C54		C55		C05					
		C42				D51		Internal cleanliness:		A:		B:		C:		D:		C57							
Location of the sample (1) Emplacement de l'échantillon Lage des Probenabschnittes 1. Front - Début - Anfang 2. Back - Fin - Ende 3. Middle - Milieu - Mitte		The delivery is in accordance with the order La fourniture est conforme aux exigences de la commande Die lieferung entspricht den Bestellbedingungen				Z01		Organisation inspection Organisme et/ou service contrôle Ueberwachungsabteilung				A05													
		Packing list Avis d'expédition Lieferscheinnummer 2023042367-102381				A10		Quality Department 7/8/2023  R. Vliegen The inspector Le responsable Der Werkssachverstaendige				Z02													
Direction of the test pieces (2) Orientation des éprouvettes Probenrichtung T. Transverse - Travers - Quer L. Longitudinal - Long - Laengs		Marking, inspection and measurement : without objection Contrôle de marquage, d'aspect et de dimensions : satisfaisants Prüfung der Stempelung, des Oberflaechenaspekts und der Abmessungen : ohne Beanstandung				D01																			